

Double seal cable glands for armoured cables (suitable for SWB-STA-Shielded) series PAPO


Execution:

Ex d / Ex e / Ex ia IIC Gb
Ex tb IIIC Db IP66

Protection degree: IP66

Atex applicable standards:

EN 60079-0, EN 60079-1, EN 60079-7,
EN 60079-31

IECEx applicable standards:

IEC 60070-0, IEC 60079-1, IEC 60079-7,
IEC 60079-31

Ambient temperature:

-60°C / +130°C with silicone sealing ring

Installation area: zone 1 – 2 (Gas)

zone 21 – 22 (Dust)

Material: Nickel plated brass or
Stainless steel

PAPO (M) INOX											
CABLE GLAND TYPE	SIZE TD ISO PITCH 1,5	CABLE GLANDS DIMENSIONS						CLAMPING RANGE		TORQUE OF CABLE GLANDS [NM]	
		H MIN	TL MIN	SW 1	SW 2	SW 3	D2 MIN	D MIN-MAX	D1 MIN-MAX	SW 2	SW 3
PAP001SMXS	M12X1,5	48,5	15	22	26	26	29	3,0-7,5	6,0-12,0	27	25
PAP001SMXS	M16X1,5	47,5	16	22	26	26	29	3,0-8,5	6,0-12,0	27	25
PAP001MXS		50	16	25	29	29	31,5	6,0-12,0	8,5-16,0	49	28
PAP01SMXS	M20X1,5	47,5	16	24	26	26	29	3,0-8,5	6,0-12,0	27	25
PAP01MXS		49	16	25	29	29	31,5	6,0-12,0	8,5-16,0	49	28
PAP01LMXS		52	16	28	30	32	35	8,5-14,5	12,0-20,0	35	28
PAP02SMXS	M25X1,5	47,5	18	29	26	26	29	3,0-8,5	6,0-12,0	27	25
PAP02SMXS		50,5	18	29	29	29	31,5	6,0-12,0	8,5-16,0	49	28
PAP02MXS		54,5	18	32	34	34	37	8,5-16,0	12,0-21,0	32	26
PAP02LMXS	M32X1,5	60,5	18	36	40	40	44	12,0-20,0	16,0-26,0	61	32
PAP03SMXS		50,5	18	36	29	29	31,5	6,0-12,0	8,5-16,0	49	28
PAP03SMXS		62	18	40	40	40	44	12,0-20,0	16,0-26,0	61	32
PAP03MXS	M40X1,5	78,5	18	48	52	52	57	15,0-26,0	20,0-33,0	86	40
PAP04SMXS		62	18	45	40	40	44	12,0-20,0	16,0-26,0	61	32
PAP04SMXS		78,5	18	48	52	52	57	15,0-26,0	20,0-33,0	86	40
PAP04MXS	M50X1,5	89,5	18	55	60	60	66	20,0-32,0	29,0-41,0	110	75
PAP05SMXS		78,4	18	54	52	52	57	15,0-26,0	20,0-33,0	86	40
PAP05MMXS		89,9	18	55	60	60	66	20,0-32,0	29,0-41,0	110	75
PAP05SMXS	M63X1,5	96,5	18	60	70	75	82	22,0-35,0	33,0-48,0	110	75
PAP05MXS		100	18	70	70	74	83	27,0-41,0	36,0-52,0	125	75
PAP06SMXS		96,5	20	68	70	75	82	22,0-35,0	33,0-48,0	110	75
PAP06MMXS	M75X1,5	100	20	70	70	74	83	27,0-41,0	36,0-52,0	125	75
PAP06SMXS		106	20	75	80	80	89,5	35,0-45,0	43,0-57,0	160	140
PAP06MXS		108	20	85	85	85	94	40,0-52,0	47,0-60,0	250	100
PAP07SMXS	M90X1,5	106	20	85	80	80	89,5	35,0-45,0	43,0-57,0	160	140
PAP07SMXS		108	20	85	85	85	94	40,0-52,0	47,0-60,0	250	100
PAP07MXS		125	20	90	95	100	110,5	45,0-60,0	54,0-70,0	250	150
PAP08SMXS	M110X1,5	108	20	100	85	85	94	40,0-52,0	47,0-60,0	250	100
PAP08SMXS		124	20	95	95	100	110,5	45,0-60,0	54,0-70,0	250	150
PAP08MXS		154	20	110	115	115	127	60,0-72,0	63,0-80,0	320	210
PAP010SMXS		124	20	120	95	100	110,5	45,0-60,0	54,0-70,0	250	150
PAP010MXS		154	20	120	115	115	127	60,0-72,0	63,0-80,0	320	210