


Execution:

Ex d / Ex e / Ex ia IIC Gb
Ex tb IIIC Db IP66

Atex applicable standards:

EN 60079-0, EN 60079-1, EN 60079-7,
EN 60079-31

Installation area: zone 1 – 2 (Gas)
zone 21 – 22 (Dust)

Protection degree: IP66

IECEx applicable standards:

IEC 60070-0, IEC 60079-1, IEC 60079-7,
IEC 60079-31

Material: Nickel plated brass or
Stainless steel

Ambient temperature:

-60°C / +80°C with silicone sealing rings
(Ex d - Ex e - Ex tb)

-60°C / +100°C with silicone sealing rings
(Ex e - Ex tb)

CODE	STAINLESS STEEL					
	CLAMPING RANGE			THREAD TYPE	SIZE	
PNAFS01M01NXS	4-6	6-9	10-12	ISO Metric - NPT	M-M16	F-3/8"
PNAFS01M12NXS	4-6	6-9	10-12	ISO Metric - NPT	M-M16	F-1/2"
PNAFS12M01NXS	4-6	6-9	10-12	ISO Metric - NPT	M-M20	F-3/8"
PNAFS1M1NXS	4-6	6-9	10-12	ISO Metric - NPT	M-M20	F-1/2"
PNAFS12M12NXS	10-12	12-14,5	14,5-16	ISO Metric - NPT	M-M20	F-1/2"
PNAFS12M23NXS	10-12	12-14,5	14,5-16	ISO Metric - NPT	M-M20	F-3/4"
PNAFS23M12NXS	10-12	12-14,5	14,5-16	ISO Metric - NPT	M-M25	F-1/2"
PNAFS2M2NXS	10-12	12-14,5	14,5-18	ISO Metric - NPT	M-M25	F-3/4"
PNAFS23M23NXS	14-17	17-20	-	ISO Metric - NPT	M-M25	F-3/4"
PNAFS23M34NXS	14-17	17-20	-	ISO Metric - NPT	M-M25	F-1"
PNAFS34M23NXS	14-17	17-20	-	ISO Metric - NPT	M-M32	F-3/4"
PNAFS3M3NXS	14-17	17-20	20-24	ISO Metric - NPT	M-M32	F-1"
PNAFS34M34NXS	22-24	24-27	28	ISO Metric - NPT	M-M32	F-1"
PNAFS34M45NXS	22-24	24-27	28	ISO Metric - NPT	M-M32	F-1 ¼"
PNAFS45M34NXS	22-24	24-27	28	ISO Metric - NPT	M-M40	F-1"
PNAFS4M4NXS	22-24	24-27	28-32	ISO Metric - NPT	M-M40	F-1 ¼"
PNAFS45M45NXS	26-28	28-31	31-34	ISO Metric - NPT	M-M40	F-1 ¼"
PNAFS45M56NXS	26-28	28-31	31-34	ISO Metric - NPT	M-M40	F-1 ½"
PNAFS56M45NXS	26-28	28-31	31-34	ISO Metric - NPT	M-M50	F-1 ¼"
PNAFS5M5NXS	26-28	28-31	31-35	ISO Metric - NPT	M-M50	F-1 ½"
PNAFS56M56NXS	35-38	38-41	41-44	ISO Metric - NPT	M-M50	F-1 ½"
PNAFS56M67NXS	35-38	38-41	41-44	ISO Metric - NPT	M-M50	F-2"
PNAFS67M56NXS	35-38	38-41	41-44	ISO Metric - NPT	M-M63	F-1 ½"
PNAFS6M6NXS	35-38	38-41	41-45	ISO Metric - NPT	M-M63	F-2"
PNAFS67M67NXS	46-48	48-52	52-56	ISO Metric - NPT	M-M63	F-2"
PNAFS67M78NXS	46-48	48-52	52-56	ISO Metric - NPT	M-M63	F-2 ½"
PNAFS78M67NXS	46-48	48-52	52-56	ISO Metric - NPT	M-M75	F-2"
PNAFS7M7NXS	46-51	51-56	56-62	ISO Metric - NPT	M-M75	F-2 ½"
PNAFS78M78NXS	60-65	65-70	-	ISO Metric - NPT	M-M75	F-2 ½"
PNAFS78M810NXS	60-65	65-70	-	ISO Metric - NPT	M-M75	F-3"
PNAFS810M78NXS	60-65	65-70	-	ISO Metric - NPT	M-M90	F-2 ½"
PNAFS8M8NXS	60-65	65-70	70-75	ISO Metric - NPT	M-M90	F-3"
PNAFS810M810NXS	75-78	78-81	81-85	ISO Metric - NPT	M-M90	F-3"
PNAFS810M10NXS	75-78	78-81	81-85	ISO Metric - NPT	M-M90	F-4"
PNAFS10M810NXS	75-78	78-81	81-85	ISO Metric - NPT	M-M100	F-3"
PNAFS10M10NXS	75-78	78-81	81-85	ISO Metric - NPT	M-M100	F-4"
PNAFS11M11NXS	85-88	88-91	91-95	ISO Metric - NPT	M-M110	F-4"

Note: Other threads are available on request


Execution:

Ex d / Ex e / Ex ia IIC Gb
Ex tb IIIC Db IP66

Atex applicable standards:

EN 60079-0, EN 60079-1, EN 60079-7,
EN 60079-31

Installation area: zone 1 – 2 (Gas)
zone 21 – 22 (Dust)

Protection degree: IP66

IECEx applicable standards:

IEC 60070-0, IEC 60079-1, IEC 60079-7,
IEC 60079-31

Material: Nickel plated brass or
Stainless steel

Ambient temperature:

-60°C / +80°C with silicone sealing rings
(Ex d - Ex e - Ex tb)

-60°C / +100°C with silicone sealing rings
(Ex e - Ex tb)

CODE	STAINLESS STEEL					
	CLAMPING RANGE			THREAD TYPE	SIZE	
PNAFS01N01NXS	4-6	6-9	10-12	NPT - NPT	M-3/8"	F-3/8"
PNAFS01N12NXS	4-6	6-9	10-12	NPT - NPT	M-3/8"	F-1/2"
PNAFS12N01NXS	4-6	6-9	10-12	NPT - NPT	M-1/2"	F-3/8"
PNAFS1N1NXS	4-6	6-9	10-12	NPT - NPT	M-1/2"	F-1/2"
PNAFS12N12NXS	10-12	12-14,5	14,5-16	NPT - NPT	M-1/2"	F-1/2"
PNAFS12N23NXS	10-12	12-14,5	14,5-16	NPT - NPT	M-1/2"	F-3/4"
PNAFS23N12NXS	10-12	12-14,5	14,5-16	NPT - NPT	M-3/4"	F-1/2"
PNAFS2N2NXS	10-12	12-14,5	14,5-18	NPT - NPT	M-3/4"	F-3/4"
PNAFS23N23NXS	14-17	17-20	-	NPT - NPT	M-3/4"	F-3/4"
PNAFS23N34NXS	14-17	17-20	-	NPT - NPT	M-3/4"	F-1"
PNAFS34N23NXS	14-17	17-20	-	NPT - NPT	M-1"	F-3/4"
PNAFS3N3NXS	14-17	17-20	20-24	NPT - NPT	M-1"	F-1"
PNAFS34N34NXS	22-24	24-27	28	NPT - NPT	M-1"	F-1"
PNAFS34N45NXS	22-24	24-27	28	NPT - NPT	M-1"	F-1 ¼"
PNAFS45N34NXS	22-24	24-27	28	NPT - NPT	M-1 ¼"	F-1"
PNAFS4N4NXS	22-24	24-27	28-32	NPT - NPT	M-1 ¼"	F-1 ¼"
PNAFS45N45NXS	26-28	28-31	31-34	NPT - NPT	M-1 ¼"	F-1 ¼"
PNAFS45N56NXS	26-28	28-31	31-34	NPT - NPT	M-1 ¼"	F-1 ½"
PNAFS56N45NXS	26-28	28-31	31-34	NPT - NPT	M-1 ½"	F-1 ¼"
PNAFS5N5NXS	26-28	28-31	31-35	NPT - NPT	M-1 ½"	F-1 ½"
PNAFS56N56NXS	35-38	38-41	41-44	NPT - NPT	M-1 ½"	F-1 ½"
PNAFS56N67NXS	35-38	38-41	41-44	NPT - NPT	M-1 ½"	F-2
PNAFS67N56NXS	35-38	38-41	41-44	NPT - NPT	M-2"	F-1 ½"
PNAFS6N6NXS	35-38	38-41	41-45	NPT - NPT	M-2"	F-2"
PNAFS67N67NXS	46-48	48-52	52-56	NPT - NPT	M-2"	F-2"
PNAFS67N78NXS	46-48	48-52	52-56	NPT - NPT	M-2"	F-2 ½"
PNAFS78N67NXS	46-48	48-52	52-56	NPT - NPT	M-2 ½"	F-2"
PNAFS7N7NXS	46-51	51-56	56-62	NPT - NPT	M-2 ½"	F-2 ½"
PNAFS78N78NXS	60-65	65-70	-	NPT - NPT	M-2 ½"	F-2 ½"
PNAFS78N810NXS	60-65	65-70	-	NPT - NPT	M-2 ½"	F-3"
PNAFS810N78NXS	60-65	65-70	-	NPT - NPT	M-3"	F-2 ½"
PNAFS8N8NXS	60-65	65-70	70-75	NPT - NPT	M-3"	F-3"
PNAFS810N810NXS	75-78	78-81	81-85	NPT - NPT	M-3"	F-3"
PNAFS810N10NXS	75-78	78-81	81-85	NPT - NPT	M-3"	F-4"
PNAFS11N810NXS	75-78	78-81	81-85	NPT - NPT	M-4"	F-3"
PNAFS10N10NXS	75-78	78-81	81-85	NPT - NPT	M-4"	F-4"
PNAFS11N11NXS	85-88	88-91	91-95	NPT - NPT	M-4"	F-4"

Note: Other threads are available on request