


Execution:

Ex d / Ex e / Ex ia IIC Gb
Ex tb IIIC Db IP66

Protection degree: IP66

Atex applicable standards:

EN 60079-0, EN 60079-1, EN 60079-7,
EN 60079-31

IECEx applicable standards:

IEC 60070-0, IEC 60079-1, IEC 60079-7,
IEC 60079-31

Ambient temperature:

-60°C / +130°C with silicone sealing rings

Installation area: zone 1 – 2 (Gas)
zone 21 – 22 (Dust)

Material: Nickel plated brass or
Stainless steel

PNAU (M) OTTONE								
CABLE GLAND TYPE	SIZE TD ISO PITCH 1,5	CABLE GLANDS DIMENSIONS					CLAMPING RANGE D MIN-MAX	TORQUE OF CABLE GLANDS [NM] SW 2
		H MIN	TL MIN	SW 1	SW 2	D1 MIN		
PNAU01MBNS	M16X1,5	25	16	22	26	29	3-8,5	31
PNAU01LMBNS		28,5	16	25	29	31,5	6-12	35
PNAU1MBNS	M20X1,5	27,5	16	25	29	31,5	6-12	35
PNAU1LMBNS		29	16	28	30	33,5	12-14,5	33
PNAU2SMBNS	M25X1,5	28,5	18	29	29	31,5	6-12	35
PNAU2MBNS		28,5	18	32	35	37	12-16	30
PNAU2LMBNS		32,5	18	36	40	44,5	12-20	61
PNAU3SMBNS	M32X1,5	33,5	18	40	40	44,5	12-20	61
PNAU3MBNS		41	18	48	52	57	15-26	86
PNAU4SMBNS	M40X1,5	41	18	48	52	57	15-26	86
PNAU4MBNS		50	18	55	60	66	20-32	110
PNAU5SMBNS	M50X1,5	50,5	18	60	70	77	22-35	110
PNAU5MBNS		54	18	70	70	77	27-41	125
PNAU6SMBNS	M63X1,5	61,5	20	75	80	89,5	35-45	165
PNAU6MBNS		61,5	20	85	85	94	40-52	250
PNAU7SMBNS	M75X1,5	61,5	20	85	85	94	40-52	250
PNAU7MBNS		72	20	90	95	105	45-60	250
PNAU8SMBNS	M90X1,5	72	20	95	95	105	45-60	250
PNAU8MBNS		84	20	110	115	127	60-72	300

PNAU (M) INOX								
CABLE GLAND TYPE	SIZE TD ISO PITCH 1,5	CABLE GLANDS DIMENSIONS					CLAMPING RANGE D MIN-MAX	TORQUE OF CABLE GLANDS [NM] SW 2
		H MIN	TL MIN	SW 1	SW 2	D1 MIN		
PNAU01MXS	M16X1,5	25	16	22	26	29	3-8,5	31
PNAU01LMXS		28,5	16	25	29	31,5	6-12	35
PNAU1MXS	M20X1,5	27,5	16	25	29	31,5	6-12	35
PNAU1LMXS		29	16	28	30	33,5	12-14,5	33
PNAU2SMXS	M25X1,5	28,5	18	29	29	31,5	6-12	35
PNAU2MXS		28,5	18	32	35	37	12-16	30
PNAU2LMXS		32,5	18	36	40	44,5	12-20	61
PNAU3SMXS	M32X1,5	33,5	18	40	40	44,5	12-20	61
PNAU3MXS		41	18	48	52	57	15-26	86
PNAU4SMXS	M40X1,5	41	18	48	52	57	15-26	86
PNAU4MXS		50	18	55	60	66	20-32	110
PNAU5SMXS	M50X1,5	50,5	18	60	70	77	22-35	110
PNAU5MXS		54	18	70	70	77	27-41	125
PNAU6SMXS	M63X1,5	61,5	20	75	80	89,5	35-45	165
PNAU6MXS		61,5	20	85	85	94	40-52	250
PNAU7SMXS	M75X1,5	61,5	20	85	85	94	40-52	250
PNAU7MXS		72	20	90	95	105	45-60	250
PNAU8SMXS	M90X1,5	72	20	95	95	105	45-60	250
PNAU8MXS		84	20	110	115	127	60-72	300