

SCELTA MATRICI

Conduttori in rame B.T.

Connettori a "C" per derivazioni / giunzioni parallele



		UTENSILI OLEODINAMICI				
Sezione conduttore mm²		HP45 (45 kN)	STILO 50, HP50 (50 kN) PP, HPI, API60-1 (60 kN)	PP, HPI, API130-H/C (130 kN)	PP230 (230 kN)	PP520 (520kN)
Passante	Derivato					
6 ÷ 2,5	6 ÷ 1,5	U4-DC6	U5-DC6			
10	10 ÷ 1,5	U4-DC10	U5-DC10	U13-DC10		
16	16 ÷ 1,5					
25 ÷ 16	10 ÷ 1,5	U4-DC25	U5-DC25	U13-DC25		
25	25 ÷ 16					
40 ÷ 35	16 ÷ 1,5					
40 ÷ 35	40 ÷ 25	U4-DC35	U5-DC35	U13-DC35		
50	25 ÷ 10					
70 ÷ 63	25 ÷ 1,5					
50	25 ÷ 4					
50	50 ÷ 35		U5-DC70	U13-DC70	Adattatore AD230-130 da utilizzare con coppia matrice da 130 kN	Adattatore AD520-130 da utilizzare con coppia matrice da 130 kN
70 ÷ 50	40 ÷ 4					
70 ÷ 50	70 ÷ 35					
100 ÷ 95	40 ÷ 4			U13-DC95		
100 ÷ 95	70 ÷ 40					
100 ÷ 95	100 ÷ 63					
125 ÷ 110	125 ÷ 25					
160 ÷ 150	125 ÷ 25			U13-DC185		
150	150 ÷ 63					
185	100 ÷ 16					

Tubetti terminali a bussola



		UTENSILI OLEODINAMICI				
Sezione conduttore mm²		HP45 (45 kN)	STILO 50, HP50 (50 kN) PP, HPI, API60-1 (60 kN)	PP, HPI, API130-H/C (130 kN)	PP230 (230 kN)	PP520 (520kN)
						
10			MTT10-50	U5-T10		
16			MTT16-50	U5-T16	MTT16-C	
25			MTT25-50	U5-T25	MTT25-C	
35			MTT35-50	U5-T35	MTT35-C	
50			MTT50-50	U5-T50	MTT50-C	
70			MTT70-50	U5-T70	MTT70-C	
95			MTT95-50	U5-T95	MTT95-C	
120				U5-T120	MTT120-C	