

SCelta MATRICI

Conduttori in rame B.T.

Capicorda tubolari con attacco a occhiello / connettori diretti



Sezione conduttore mm ²		UTENSILI OLEODINAMICI					
		HP45 (45 kN)	STILO 50, HP50 (50 kN) PP, HPI, API60-1 (60 kN)		PP, HPI, API130-H/C (130 kN)	PP230 (230 kN)	PP520 (520kN)
rigido	flessibile						
6		MK5-45	MK5-50				
10		U4-K07M	U5-K07M	U5-I10	U13-K07M		
16		U4-K08M	U5-K08M	U5-I16	U13-K08M		
25		U4-K10M	U5-K10M	U5-I25	U13-K10M		
35	25 35	U4-K11M	U5-K11M	U5-I35	U13-K11M		
50	35 50	U4-K13M	U5-K13M	U5-I50	U13-K13M		
70	50 70	U4-K14	U5-K14	U5-I70	U13-K14	Adattatore AD230-130 da utilizzare con coppia matrice da 130 kN	Adattatore AD520-130 da utilizzare con coppia matrice da 130 kN
95	70 95	U4-K17M	U5-K17M	U5-I95	U13-K17M		
120	95 120	U4-K18	U5-K18	U5-I120	U13-K18		
150	120 150	U4-K20D	U5-K20D	U5-I150	U13-K20D		
185	150 185		U5-K22D	U5-I185	U13-K22D		
240	185 240		U5-K25M	U5-I240	U13-K25M		
300	240 300				U13-K28D		
400	300				U13-K34D	MK34-230	MK34-520
500	400					MK38-230	MK38-520
630	500					MK42-230	MK42-520
800	630					MK44-230	MK44-520