

SAITEX-MR

Manicotti cilindrici rinforzati di tela abrasiva
Manchons cylindriques renforcés en toile abrasive
 Interlined abrasive cloth sleeves
Manguitos cilindricos reforzados de tela abrasiva



Z-X

Tela con zirconio, doppia resina.
 Utilizzo con pressioni di lavoro
 elevate.

Toile au zirconium, double résine.
Utilisation avec pressions de travail
élevées.

Full resin bonded zirconia cloth.
 For operations in heavy duty
 applications.

Tela en zirconio, doble resina. Uso
con presiones de trabajo elevadas.

APPLICAZIONI

- ACCIAI
- ACCIAI LEGATI
- ACCIAI INOSSIDABILI
- METALLI NON FERROSI
- CUOIO E PELLI
- ▲ GHISE

PRÉCONISATIONS

- ACIERS
- ACIERS ALLIÉS
- ACIERS INOXYDABLES
- MÉTAUX NON FERREUX
- CUIR ET PEaux
- ▲ FONTES


APPLICATIONS

- STEELS
- ALLOY STEELS
- STAINLESS STEELS
- NON-FERROUS METALS
- LEATHER
- ▲ CAST IRON

APLICACIONES

- ACEROS
- ACEROS ALEADOS
- ACEROS INOXIDABLES
- METALES NO FÉRRICOS
- CUERO Y PIELS
- ▲ FUNDICIONES

		Ø x H				
SAITEX-MR	Z-X	10 x 10	80	38088	stock	200 (4x50)
SAITEX-MR	Z-X	10 x 10	120	38234	W4	200 (4x50)
SAITEX-MR	Z-X	10 x 20	80	38089	stock	200 (4x50)
SAITEX-MR	Z-X	10 x 20	120	38235	stock	200 (4x50)
SAITEX-MR	Z-X	15 x 30	50	38093	stock	200 (2x100)
SAITEX-MR	Z-X	15 x 30	60	38092	stock	200 (2x100)
SAITEX-MR	Z-X	15 x 30	80	38091	stock	200 (2x100)
SAITEX-MR	Z-X	15 x 30	120	38237	stock	200 (2x100)
SAITEX-MR	Z-X	22 x 20	50	38096	stock	200 (2x100)
SAITEX-MR	Z-X	22 x 20	60	38095	stock	200 (2x100)
SAITEX-MR	Z-X	22 x 20	80	38094	stock	200 (2x100)
SAITEX-MR	Z-X	22 x 20	120	38238	W4	200 (2x100)
SAITEX-MR	Z-X	30 x 20	40	38100	W4	200 (4x50)
SAITEX-MR	Z-X	30 x 20	60	38098	W4	200 (4x50)
SAITEX-MR	Z-X	30 x 20	80	38097	W4	200 (4x50)
SAITEX-MR	Z-X	30 x 30	40	38084	stock	200 (4x50)
SAITEX-MR	Z-X	30 x 30	50	38102	stock	200 (4x50)
SAITEX-MR	Z-X	30 x 30	60	38085	stock	200 (4x50)
SAITEX-MR	Z-X	30 x 30	80	38101	stock	200 (4x50)
SAITEX-MR	Z-X	30 x 30	120	38240	stock	200 (4x50)
SAITEX-MR	Z-X	45 x 30	40	38086	stock	200 (4x50)
SAITEX-MR	Z-X	45 x 30	50	38104	W4	200 (4x50)
SAITEX-MR	Z-X	45 x 30	60	38087	stock	200 (4x50)
SAITEX-MR	Z-X	45 x 30	80	38103	stock	200 (4x50)
SAITEX-MR	Z-X	45 x 30	120	38241	stock	200 (4x50)



■ applicazioni principali / *préconisations principales* / main applications / *aplicaciones principales*
 ▲ possibile utilizzo / *utilisations possibles* / possible use / *posible uso*

SAITEX-MR

Manicotti cilindrici rinforzati di tela abrasiva
Manchons cylindriques renforcés en toile abrasive
 Interlined abrasive cloth sleeves
Manguitos cilindricos reforzados de tela abrasiva



3A-X

Tela con corindone speciale, doppia resina, filled.

Toile en corindon spécial, double résine, lubrifiée.

Full resin bonded special aluminium oxide cloth, filled.

Tela en corindón especial, doble resina, filled.

APPLICAZIONI

- ACCIAI INOSSIDABILI
- ACCIAI LEGATI
- ▲ METALLI NON FERROSI

PRÉCONISATIONS

- ACIERS INOXYDABLES
- ACIERS ALLIÉS
- ▲ MÉTAUX NON FERREUX

APPLICATIONS

- STAINLESS STEELS
- ALLOY STEELS
- ▲ NON-FERROUS METALS

APLICACIONES

- ACEROS INOXIDABLES
- ACEROS ALEADOS
- ▲ METALES NO FÉRRICOS

		Ø x H					
SAITEX-MR	3A-X	10 x 20	P-80	38215	stock		200 (4x50)
SAITEX-MR	3A-X	10 x 20	P-120	38216	W4		200 (4x50)
SAITEX-MR	3A-X	15 x 30	P-50	38219 °	stock		200 (2x100)
SAITEX-MR	3A-X	15 x 30	P-60	38220	stock		200 (2x100)
SAITEX-MR	3A-X	15 x 30	P-80	38194	stock		200 (2x100)
SAITEX-MR	3A-X	15 x 30	P-120	38221	W4		200 (2x100)
SAITEX-MR	3A-X	22 x 20	P-50	38222 °	stock		200 (2x100)
SAITEX-MR	3A-X	22 x 20	P-60	38133	W4		200 (2x100)
SAITEX-MR	3A-X	22 x 20	P-80	38196	stock		200 (2x100)
SAITEX-MR	3A-X	22 x 20	P-120	38197	W4		200 (2x100)
SAITEX-MR	3A-X	30 x 30	P-40	38069	stock		200 (4x50)
SAITEX-MR	3A-X	30 x 30	P-50	38131 °	W4		200 (4x50)
SAITEX-MR	3A-X	30 x 30	P-60	38127	stock		200 (4x50)
SAITEX-MR	3A-X	30 x 30	P-80	38190	stock		200 (4x50)
SAITEX-MR	3A-X	45 x 30	P-40	38183	stock		200 (4x50)
SAITEX-MR	3A-X	45 x 30	P-50	38224 °	stock		200 (4x50)
SAITEX-MR	3A-X	45 x 30	P-60	38134	stock		200 (4x50)

9S-J

Tela in polycotton con abrasivo ceramico, doppia resina, **top-filled**. Utilizzo con pressioni di lavoro leggere. Basso surriscaldamento. Buona flessibilità.

Toile en polycoton avec abrasif céramique, double résine, auto-lubrifiée. Utilisation sous pressions de travail légers. Faible suréchauffement. Bonne flexibilité.

Full resin bonded polycotton cloth with ceramic abrasive, **top-filled**, for operations in light duty applications. Low heat generation. Good flexibility.

Tela en polyalgodón con abrasivo cerámico, doble resina, top-filled. Usar con presiones de trabajo ligeras. Bajo calentamiento. Buena flexibilidad.

APPLICAZIONI

- ACCIAI INOSSIDABILI
- ACCIAI LEGATI

PRÉCONISATIONS

- ACIERS INOXYDABLES
- ACIERS ALLIÉS


APPLICATIONS

- STAINLESS STEELS
- ALLOY STEELS

APLICACIONES

- ACEROS INOXIDABLES
- ACEROS ALEADOS

		Ø x H					
SAITEX-MR	9S-J	22 x 20	60	38003 °	W4		200 (2x100)
SAITEX-MR	9S-J	22 x 20	80	38004	W4		200 (2x100)
SAITEX-MR	9S-J	22 x 20	120	38006	W4		200 (2x100)



- applicazioni principali / *préconisations principales* / main applications / *aplicaciones principales*
- ▲ possibile utilizzo / *utilisations possibles* / possible use / *posible uso*