


Execution:

Ex d / Ex e / Ex ia IIC Gb
Ex tb IIIC Db IP66

Atex applicable standards:

EN 60079-0, EN 60079-1, EN 60079-7,
EN 60079-31

Installation area: zone 1 – 2 (Gas)
zone 21 – 22 (Dust)

Protection degree: IP66

IECEx applicable standards:

IEC 60070-0, IEC 60079-1, IEC 60079-7,
IEC 60079-31

Material: Nickel plated brass or
Stainless steel

Ambient temperature:

-60°C / +80°C with silicone sealing rings

CODE	NICKEL PLATED BRASS				
	CLAMPING RANGE			THREAD TYPE	SIZE
PNAC0SNBNS*	4-6	6-8	-	NPT	1/4"
PNAC01NBNS	4-6	6-9	9-12	NPT	3/8"
PNAC1NBNS	4-6	6-9	9-12	NPT	1/2"
PNAC12NBNS	10-12	12-14,5	14,5-16	NPT	1/2"
PNAC2NBNS	10-12	12-14,5	14,5-18	NPT	3/4"
PNAC23NBNS	14-17	17-20	-	NPT	3/4"
PNAC3NBNS	14-17	17-20	20-24	NPT	1"
PNAC34NBNS	22-24	24-27	-	NPT	1"
PNAC4NBNS	22-24	24-27	27-32	NPT	1 ¼"
PNAC45NBNS	26-28	28-31	31-34	NPT	1 ¼"
PNAC5NBNS	26-28	28-31	31-35	NPT	1 ½"
PNAC56NBNS	35-38	38-41	-	NPT	1 ½"
PNAC6NBNS	35-38	38-41	41-45	NPT	2"
PNAC7NBNS	46-51	51-57	57-59	NPT	2 ½"

(*) Only Ex e / Ex tb execution (-60°C / +100°C with silicone sealing rings)

Note: Other threads are available on request

CODE	STAINLESS STEEL				
	CLAMPING RANGE			THREAD TYPE	SIZE
PNAC0SNXS*	4-6	6-8	-	NPT	1/4"
PNAC01NXS	4-6	6-9	9-12	NPT	3/8"
PNAC1NXS	4-6	6-9	9-12	NPT	1/2"
PNAC12NXS	10-12	12-14,5	14,5-16	NPT	1/2"
PNAC2NXS	10-12	12-14,5	14,5-18	NPT	3/4"
PNAC23NXS	14-17	17-20	-	NPT	3/4"
PNAC3NXS	14-17	17-20	20-24	NPT	1"
PNAC34NXS	22-24	24-27	-	NPT	1"
PNAC4NXS	22-24	24-27	27-32	NPT	1 ¼"
PNAC45NXS	26-28	28-31	31-34	NPT	1 ¼"
PNAC5NXS	26-28	28-31	31-35	NPT	1 ½"
PNAC56NXS	35-38	38-41	-	NPT	1 ½"
PNAC6NXS	35-38	38-41	41-45	NPT	2"
PNAC7NXS	46-51	51-57	57-59	NPT	2 ½"

(*) Only Ex e / Ex tb execution (-60°C / +100°C with silicone sealing rings)

Note: Other threads are available on request